

SYSTEM SPECIFICATIONS

System Type	5-axis gyro-stabilized, Full Digital Servo and Control System, High Performance/ Small/Lightweight
Field of Regard	Automatic and Steerable
Azimuth Coverage	360° Continuous
Elevation Coverage	+20° to -195°
Roll Coverage	+/- 45°
Slew Rate	>55°/sec
Maximum Slew Acceleration	100°/sec(squared)
Position Resolution	.001°
Electronics	High Speed 32bit DSP
Communication Links	Bi-directional RS422 and RS232
Operating Temperature	-20° to +45° C

HD DAYLIGHT IMAGER

Camera	Sony HDC-1500
Imaging Device	3-CCD 2/3"
Effective Pixels	1920(H) x 1080(V)
Aspect Ratio	16:9
Frame Rates	1080/60p-50p-30p, 1080/60i-50i, 1080/24p-25p, 720/60p-50p
Spectrum System	F1.4 prism system
Built In Filters	1: Clear, 2: 1/4ND, 3:1/8ND, 4:1/16ND, 5:1/64ND A: Cross, B: 3200K, C: 4300K, 0: 6300K, E:8000K
Servo Filter Control	Yes
Sensitivity	F10 at 2000 lx (3200k, 89.9% reflectance)
Signal-To-Noise Ratio	54dB (typical)
Horizontal	1000 TV lines

DIMENSIONS

Item	Weight	Dimensions
Turret (dependent on lens)	65-68 lbs.	14.5" x 19.5" x 19.5"
Auxiliary Control Unit	27lbs.	14" x 19" x 6"
Laptop Control Unit	5lbs.	11" x 8.75" x 1.8"
Cable Set	9lbs.	(20' length)

POWER

Input Voltage	28 Vdc ± 10%
Power - Quiescent	85 Watts
Power - Continuous	170 Watts
Power - Transient	230 Watts

MAIN CONTROL UNIT

Interface	Digital serial (RS-422)
------------------	-------------------------

INCORPORATED CAMERA ACCESSORIES

Sony HKC-T1500 CCD	Block Extension Adaptor
Sony RM-B750	LCD touch-panel screen, direct push buttons plus Memory Stick~ media card slot to recall setup parameters

LENS OPTIONS

Fujinon~ HA 42 x 9.7	(9.7mm to 815mm optical, 1630mm digital)
Fujinon~ HA 13 x 4.5	(4.5mm to 117mm optical, 234mm digital)